How to Sync a Resolution Field in Jira Cloud

Last Modified on 04/09/2024 10:33 am EDT

This article shows how to synchronize the issue resolution field in Jira.

Introduction

Whenever you need to sync the resolution, you have to ensure that the resolution from the remote side is mapped to the local resolution objects.

Source Side

Add the code below to the **Outgoing sync** to send a resolution to the other side.

```
replica.resolution = issue.resolution
```

Destination Side

Add the code below to the **Incoming sync** to set the resolution for the synced issue, based on the source side data.

```
if (replica.resolution == null) {
    // if the remote issue is not resolved
    issue.resolution = null
}
if (replica.resolution != null) {
    // the remote issue is resolved, but the local isn't - look up the correct local resolution object.

def resolutionMap = [
    "Done" : "Done",
    "Won't Do" : "Won't Do",
    "Known Error" : "Won't Fix"
    // use 'done' as resolution if the remote resolution is not found
    def targetResolutionName = resolutionMap[replica.resolution.name] ?: "Done"
    // nodeHelper.getResolution looks up the local resolution object based on the provided name
    issue.resolution = nodeHelper.getResolution(targetResolutionName)
}
```

You can also just hardcode a resolution by name:

```
if (replica.resolution == null) {
    // if the remote issue is not resolved
    issue.resolution = null
}
if (replica.resolution != null) {
    issue.resolution = nodeHelper.getResolution("Fixed")
}
```

ON THIS PAGE

 Release tistory [2]

 Source Side

 Source Side

 Spectime [2]

 Dectime [2]

 Resources

 Subscribe for a weekly Exalate hack [2]

 Academy [2]

 Blog [3]

 YouTube Channel [2]

 Ebooks [3]

Still need help? Join our Community 🖓 Visit our Service Desk 🖓 Find a Partner 🖓