

Initiate a Private Connection in Script Mode for Salesforce

Last Modified on 01/15/2026 8:07 pm EST


Note: For Private Connections:

- an instance you have access to is considered a public side.
- an instance you don't have access to is considered a private side: destination instance.

The main difference between private and public connection types is whether the HTTP/HTTPS requests are initiated from one side or from both sides. In this case, HTTP/HTTPS requests are initiated from the destination's private side only.

Initiate a Private Connection from Salesforce

1. Navigate to the **Connections** tab in the Exalate console.




Click **Connections**.

2. Click **Initiate Connection**.



3. Click **I don't have a URL**

If the destination instance is in a private network click **I don't have a URL**.



Initiate connection


Destination instance URL ⓘ

I don't have a URL

Next

4. Choose a **Basic** connection mode.

5. Click **Next**.



Initiate connection

Destination instance URL ⓘ

I don't have a URL

Choose the configuration type

Basic

- Automatic configuration of basic fields
- Sync rules cannot be edited
- Only issues can be synced
- Recommended for use cases of basic complexity

Script

- Groovy-based scripting
- Configure each side of the connection separately
- Recommended for use cases of basic to advanced complexity

Next

6. Click **Next**.

Note: As this is a Public-Private connection and you don't have admin access to the other side, you can continue to configure on your end and then send an invitation to your partner.

7. Enter Connection information & Click **Next**

Field	Description
Local instance short name	A short name for your instance

Field	Description
Destination instance short name	A short name for the destination instance
Connection name	Name of the connection
Description	Description of the connection

Initiate connection x

Connection information

Local instance short name*

Remote instance short name* ?

Connection name*

Description

◀ Previous Next ▶

8. Click **Copy Invitation Code**

Here you can copy the invitation code and send it over to your partner. The destination side will be shown as "unknown" since this is a private side.

Initiate connection x

Ensure that Exalate is [installed](#) on the destination side "unknown"

On the "unknown" side, you (or their application administrator) need to [Accept the invitation](#).

Use the following invitation code:

[Copy invitation code](#)

Done

9. Click **Done**

Once your partner accepts the invitation, you can start synchronization.

Product

[About Us ?](#) **Note:** When the connection is set up on the Public source side, the Private side administrator should accept the invitation in the Private-Public connection.

[Release History ?](#)

[Glossary ?](#)

[API Reference ?](#)

[Security ?](#)

[Pricing and Licensing ?](#)

Resources

[Subscribe for a weekly Exalate hack ?](#)

[Academy ?](#)

[Blog ?](#)

[YouTube Channel ?](#)

[Ebooks ?](#)

Still need help?

[Join our Community ?](#)

[Visit our Service Desk ?](#)

[Find a Partner ?](#)