

# Sync an Assignee to a Text Custom Field in Exalate for Jira on-premise

Last Modified on 01/15/2026 6:02 pm EST

This article shows how to synchronize an assignee to a text custom field.

## Source side

### Outgoing sync

```
replica.assignee = issue.assignee
```

## Destination side

An assignee is an object with some properties. Each property is of type text. You can sync the following properties: key, email, displayName, username. Add the code below to the **Incoming sync** to sync Assignee email address.

```
issue.customFields."Your custom field name".value = replica.assignee?.email
```

You can replace the .email property with any other assignee object property.

Check [User](#) for all available properties. For example, to sync the assignee displayName use this code.

```
issue.customFields."Your custom field name".value = replica.assignee?.displayName
```

### Product

[About Us](#) ?

### ON THIS PAGE

[Release History](#) ?

[Glossary](#) ?

[Source side](#)

[API Reference](#) ?

[Destination side](#)

[Security](#) ?

[Pricing and Licensing](#) ?

### Resources

[Subscribe for a weekly Exalate hack](#) ?

[Academy](#) ?

[Blog](#) ?

[YouTube Channel](#) ?

[Ebooks](#) ?

### Still need help?

[Join our Community](#) ?

[Visit our Service Desk](#) ?

[Find a Partner](#) ?