

getUser

Last Modified on 01/15/2026 4:37 pm EST

Note: For the method to work on Azure DevOps, make sure that the user is part of the team that has access to the Azure DevOps project.

Signature

Helper	nodeHelper
Signature	<p>Jira Server: <code>getUser(String userKey)</code></p> <p>Jira Cloud: <code>getUser(String accountId)</code></p> <p>Azure DevOps:</p> <p><code>getUser(String userKey), getUserByUsername(username: String)</code> is the same as <code>getUserByFullName(username: String)</code></p> <p>Salesforce: <code>getUser(String userKey)</code></p>
Description	Returns a user object Null in case the user is not found
Introduced in	0.8

Note: The Signature introduced in 0.8 works for Azure Devops until version 5.4.0.

Example use

Product

Set the local issue assignee based on the remote issue assignee using the method.

[Release History](#) 

[Glossary](#) 

```
issue.assignee = nodeHelper.getUser(replica.assignee.key)
```

[Security](#) 

[Pricing and Licensing](#) 

Resources

[Subscribe for a weekly Exalate hack](#) 

[Academy](#) 

[Blog](#) 

[YouTube Channel](#) 

[Ebooks](#) 

Still need help?

[Join our Community](#) 

[Visit our Service Desk](#) 

[Find a Partner](#) 