

getCustomFieldDefaultValue

Last Modified on 01/30/2026 11:09 am EST

h2 id="getCustomFieldDefaultValue-Signature">Signature

Helper	nodeHelper
Signature	There are multiple signature options: <code>getCustomFieldDefaultValue(String name, IHubIssueType type, IHubProject project)</code> <code>getCustomFieldDefaultValue(Long id, IHubIssueType type, IHubProject project)</code> <code>getCustomFieldDefaultValue(String name, IHubIssue issue)</code> <code>getCustomFieldDefaultValue(Long id, IHubIssue issue)</code>
Description	Returns the default value of the customfield
Introduced in	0.9.1

Example use

```
issue.project = nodeHelper.getProject("Staff")
issue.issueType = nodeHelper.getIssueType("Hobby")

if (replica.customKey.mood == null) {
    issue.customFields.mood.value = nodeHelper.getCustomFieldDefaultValue("mood", issue.issueType, issue.project)
}
```

[API Reference](#)

[Security](#)

[Pricing and Licensing](#)

Resources

[Subscribe for a weekly Exalate hack](#)

[Academy](#)

[Blog](#)

[YouTube Channel](#)

[Ebooks](#)

Still need help?

[Join our Community](#)

[Visit our Service Desk](#)

[Find a Partner](#)