

# How to Sync Sub-tasks between Jira On-Premise and Jira Cloud

Last Modified on 01/15/2026 3:27 pm EST

This article shows examples of how to sync sub-tasks between Jira On-Premise and Jira Cloud.

**Warning:** Despite our best efforts, code can change without notice due to a variety of factors. If you encounter an issue in any of the code shown here and find that a specific block of code is not correct, or is causing errors, please check with the [Community](#) to find an updated version.

## Syncing Sub-tasks between Jira On-Premise and Jira Cloud

To exchange sub-tasks between Jira-On-Premise and Jira Cloud, you need to specify the mapping for sending the parent id from one side and receive that parent id on target side to find its corresponding id .

### Jira On-Premise

#### Outgoing sync

```
replica.parentId = issue.parentId
```

#### Incoming sync

```
if(firstSync){
    issue.projectKey = "ABC"
    // Set type name from source issue, if not found set a default
    issue.typeName = nodeHelper.getIssueType(replica.type?.name, issue.projectKey)?.name ?: "Task"
    if(firstSync && replica.parentId){
        issue.parentId = null
        if (replica.parentId){
            //localParent = syncHelper.getLocalIssueKeyFromRemoteld(replica.parentId)
            localParent = nodeHelper.getLocalIssueKeyFromRemoteld(replica.parentId,"issue")
            //debug.error("localParent"+localParent)
            if (localParent){
                issue.parentId = localParent.id
                issue.typeName = "Sub-task"
            }
            else {
                throw new com.exalate.api.exception.IssueTrackerException("Subtask cannot be created: parent issue with remote id " + replica.parentId + " was not found. Please make sure the parent issue is synchronized before resolving this error" )
            }
        }
    }
    issue.summary = replica.summary
    ....
```

# Jira Cloud

## Outgoing sync

```
if(issue.typeName == "Sub-task" && issue.parentId == null) return
replica.key = issue.key
replica.type = issue.type
.....
replica.parentId = issue.parentId
.....
```

**Note:** The first line needs to be added because Jira Cloud initially creates the subtask without a parent Id. The lack of a parentId would result in failure on other side .

## Incoming sync

```
if (firstSync) {
    issue.projectKey = "XYZ"
    def issueType = replica.type?.name.toString()
    issue.typeName = nodeHelper.getIssueType(replica.type?.name, issue.projectKey)?.name ?: "Task"
    if(firstSync && replica.parentId) {
        issue.parentId = null
        if (replica.parentId) {
            localParent = syncHelper.getLocalIssueKeyFromRemoteld(replica.parentId)
            if (localParent) {
                issue.parentId = localParent.id
                issue.typeName = "Sub-task" //Make sure to use the right subtask type here.
            }
        }
    } else {
        throw new com.exalate.api.exception.IssueTrackerException("Subtask cannot be created: parent issue with remote id " + replica.parentId + " was not found. Please make sure the parent issue is synchronized before resolving this error")
    }
}
issue.summary = replica.summary
....
```

**Note:** Both the parent task and the sub-task must be in sync for the parent link to be created in the child issue.

Product

[About Us](#)

ON THIS PAGE

[Release History](#)

[Glossary](#)

[Syncing Sub-tasks between Jira On-Premise and Jira](#)

[API Reference](#)

[Cloud](#)

[Security](#)

[Pricing and Licensing](#)

Resources

[Subscribe for a weekly Exalate hack](#) 

[Academy](#) 

[Blog](#) 

[YouTube Channel](#) 

[Ebooks](#) 

**Still need help?**

[Join our Community](#) 

[Visit our Service Desk](#) 

[Find a Partner](#) 